

8000T Magnetic Tag

Features:

- Thermal transfer, printable magnet
- Excellent smear/scratch resistance
- Excellent chemical resistance
- Sticks best to iron, steel, or other magnetic surfaces
- Will not stick to stainless steel or aluminum surfaces
- Available in white (10026049RM)

Suggested Applications:

- Work in Process
- Reusable tote labeling
- Applications requiring clean removability
- Temporary Rack labeling
- Flex-space labeling

Material Construction:

Description	Caliper
Facestock	Thermal transfer printable magnet
	12.0 mil
Total	12.0 mil +/- 10%

Temperature Performance:

- Minimum Application Temperature: -15° F (-26° C)
- Service Temperature: -15° F to 160° F (-26° C to 70° C)
- Optimal Storage Conditions: 72° F (22° C) at 50% RH
- Expected Exterior Life: Up to 1 year

Suggested Ribbons for Applications with Chemicals

	Weak					Moderate				Harsh			Extreme				
	Blood	Body Fluid	Salt Water	Water	Window Cleaner	Alcohol	Ammonia	Bleach	IPA	Gasoline	Grease	Oil	Acetone	IR Reflow	MEK	TCE	Xylene
5095	X	X	X	X	X	X	X	X	X		X	X					

Additional Technical Information:

Magnet pull strength – 20 lb/sq ft

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.